

SP90

Audiometric Speaker System

#8100693

Features

- RoHS compatible
- Robust design
- Easy to use
- Thick MDF walls
- Reduced sound reflection
- Protective metal grills
- Rounded corners



The Gold Standard
of Audiometric Transducers


S90 Passive Audiometric Full Range Speaker System

- RadioEar brings you the compact audiometric speakers with the immense performance.
- Superb sound quality and specification.
- Cleverly shaped to fit perfectly in to your office or sound room environment.
- Robust and durable design with no compromise on style.

SP90

Technical Specifications

S90 Output and Impedance




Graph 1: Typical Frequency Response

Attractive space-saving design with a durable construction and superior quality make the SP90 speaker system the perfect office or sound room companion.

Dynamic Speaker 8 ohm

Power Input:	40 W continuous 80 W peak
Connections:	Red /Black spring-loaded connector for bare end wire
Total Harmonic Distortion:	<1% at 1 W < 5% at rated power
Frequency Response:	125 Hz - 8 kHz
Sensitivity:	94 dB/1 W
Impedance:	8 ohm
Dimensions (each):	(H) 13.78" (350 mm) x (W) 13.78" (350 mm) x (D) 5.12" (130 mm)
Weight:	10.23 lbs/4.6 kg
Materials and Construction:	<ul style="list-style-type: none">• 12 mm thick MDF cabinet• 6.5" full-range driver



Included Accessories

- Cable 157.5"
- Cable Fasteners
- Mounting Brackets with Screws
- Set-Up Guide